



THE COMPLETE DUCT SOURCE

Quality—Delivery—Service—Design—Price

US Duct—Gates

US Duct Auto Gates are pneumatically operated— electrically controlled. The pneumatic cylinders require 90 psi to operate but use very little volume. An electric solenoid directs the flow of the air to the cylinder for opening and closing. The solenoid is activated by virtually any electrical signal— 12/24 V AC/DC, or 110/220 line voltage. The solenoid operates off of milliamps and therefore requires only minimal wiring. Hook up to anything that becomes ‘hot’ when the gate is required to be open. (or closed.)

DIA.	A	B	C*	# CYL
3"	14"	5"	5 1/4"	1
4"	18"	6"	5 1/4"	1
5"	22 1/2"	6 5/8"	5 1/4"	1
6"	26"	7 3/4"	5 1/4"	1
7"	27"	9"	5 1/4"	1
8"	28 1/2"	10"	5 1/4"	1

DIA.	A	B	C	# CYL
9"	17"	14 1/2"	5 1/4"	2
10"	17 1/2"	15 1/2"	5 1/4"	2
11"	17 1/2"	16 1/2"	5 1/4"	2
12"	18 3/4"	17"	5 1/4"	2
13"	23"	21 1/2"	5 1/4"	2
14"	23"	21 1/2"	5 1/4"	2
15"	24"	24"	5 1/4"	2
16"	24"	24"	5 1/4"	2
17"	38"	26"	5 1/4"	2
18"	38"	26"	5 1/4"	2
20"	39"	28"	5 1/4"	2
22"	39"	31"	5 1/4"	2
24"	39"	35"	5 1/4"	2
LARGER	CALL			2

